



553001

## Analog ORP/pH Controller

### INCLUDES:


Controller, flow cell, probes,  
1/4" tubing, fittings.

**ORP/pH Analog Controller maintains  
ORP and pH levels and monitors both  
with red light bar indicators**

For Use With Liquid Chlorine & Acid,  
Calhypo & Acid or Bromine & Acid



ORP/pH Analog Control System



**ROLA-CHEM  
CORPORATION**

**PROVIDES ALL THESE FEATURES  
AT A VERY AFFORDABLE PRICE.**

### WORLD CLASS ACCEPTANCE

- Uses ORP technology
- Redox sensor

### CONTROLS BY MEASURING THE ACTUAL SANITIZING POWER

### SIMPLE TO OPERATE

- Two LED light bars
- Two control knobs
- Two switches

### NO CALIBRATION REQUIRED

- Simply manually set pool to desired standards (i.e. 7.5 pH 2-3 ppm chlorine, 700-750MV ORP) and the Rola-Chem controller will hold the pool to these ranges

### COST EFFECTIVE

- Feeding only the required amount of chemicals for effective pool sanitizing can help to save on chemical usage

### QUICK INSTALLATION MANIFOLD KIT INCLUDES

- Manifold, ORP & pH probes, three quick connect valves, 40 feet of 1/4" tubing and two tubing connectors

THE ROLA-CHEM CONTROLLER IS COMPATIBLE  
WITH MOST PERISTALTIC PUMPS

RUGGED, SEALED, CORROSION-RESISTANT  
PLASTIC HOUSING

### MAINTENANCE MODE

- Allows manual operation of pump while still monitoring ORP & pH

AUDIBLE ALARM CAN BE TURNED OFF OR ON AS DESIRED

### INCLUDES TWO CRITICAL SAFETY SHUTOFFS

- Ten-minute out-of-range of upper or lower limits
- Two-hour in-range failure to maintain pool

### WARRANTY

- One-year limited warranty on electronics

**NOTE:** Rola-Chem Analog models come with non-flow switch flow cell. Probes come with a 90-day warranty (one-year warranty optional).

**NOTE:** It is recommended that an in-line filter system be used before the flow cell.

**NOTE:** It is recommended that an auxiliary flow switch be used with the Analog System