

ROLA-CHEM GENERATION II

DIGITAL ORP/pH CONTROLLER



554000
Digital ORP/pH Controller

INCLUDES:
 Controller, flow cell with flow switch,
 probes, 3/8" tubing, fittings.



TECHNICAL SPECIFICATIONS:

	pH	ORP	Feed Cycle
• Factory Setting:	7.4	650 mV	.6 sec.
• Display Range:	6.8 – 8.2	0 – 995 mV	
• Setpoint Range:	7.0 – 8.0	400 – 900 mV	
• Feed Cycle Range:	.6 to 900 sec with 5-minute timeouts		
• Power:	120V corded		
• Feed:	Automatic or manual		
• Maximum Amps:	5 Amps		
• Probes:	One-year limited warranty		
• Warranty:	One-year limited warranty on electronics		

Ready-To-Mount Wall System

CONTAINS:

Controller, flow cell with flow switch,
 probes, 40' of 3/8" tubing, fittings and
 2 peristaltic pumps.

- Mounting board is pre-drilled and ready to mount on wall
- **NOTE: when ordering the Ready-To-Mount Wall System, it is necessary to order the individual component part numbers.**
- **NOTE: It is recommended that an in-line filter system be used before the flow cell.**

DIGITAL ORP/pH
 CONTROLLER
FEATURES:

- Digital readouts
- ORP technology
- Redox sensor
- Proportional feed
- Dip switch programmable settings
- Flow switch included
- Lockout security feature
- Built-in out-of-range safety timeouts
- pH calibration
- Acid or base feed
- Microprocessor logic
- Globe flow cell with flow switch
- Compatible with most peristaltic pumps
- Can also be used with erosion feeder/solenoid applications

