

PROFESSIONAL pH SYSTEM CONTROLLER

FOR SANITIZING SWIMMING POOLS AND SPAS

NEW



554200

Digital pH Controller

Designed to be used for pH control where Chlorine Generator (Salt System) is installed.

INCLUDES:

Controller, flow cell with flow switch, pH probe, 3/8" tubing, fittings. Peristaltic Pump is extra.

- **Probes: One-year limited warranty**
- **Warranty: One-year limited warranty on electronics**
- **NOTE: It is recommended that an in-line filter system be used before the flow cell**

DIGITAL pH CONTROLLER FEATURES:

- pH Monitoring from 6.8 pH to 8.2 pH with .1 pH Resolution
- Set Level from 7.0 pH to 8.0 pH
- Dosing Options from Continuous to up to 15 Minutes
- Factory Set 5 Minute Delay in Timed Feed Mode
- Factory Set High (8.0 pH) and Low (7.0 pH) Alert Levels
- Single Button Calibration
- Overfeed Alert after 30 Minutes in Continuous Feed and 30 Feed Cycles in Timed Feed Mode (Requires Hard Reset)
- Easy to Read, Sun-Bright LED Display
- Configure for Acid or Base (Jumper)
- Compact Package (Approx. 7" x 5" x 3")
- Configure for 120 VAC (Input/Output)
- Flow Switch Compatible
- Bright LED Indicators for Feed, Alert and Flow
- Manufactured in the USA