

DIGITAL pH CONTROLLER WALL SYSTEM

RECOMMENDED FOR USE WITH CHLORINE (SALT) GENERATORS



554200

Digital pH Controller

Designed to be used for pH control where Chlorine Generator (Salt System) is installed.

INCLUDES: Controller, flow cell with flow switch, pH probe, 3/8" tubing, fittings.

- **Probes: One-year limited warranty**
- **Controller: One-year limited warranty on electronics**
- **NOTE: It is recommended that an in-line filter system be used before the flow cell**



554217

Ready-To-Mount Wall System

INCLUDES: Controller, flow cell with flow switch, pH probe, 40' of 3/8" tubing, fittings and one 32 GPD peristaltic pump.

- Mounting board is pre-drilled and ready to mount on wall
- **NOTE: This system is designed to control pools up to 100,000 gallons. Larger pools may require larger GPD peristaltic pumps**
- **NOTE: It is recommended that an in-line filter system be used before the flow cell (see page 5)**

554114

Mounting Board with mounting screws

DIGITAL pH CONTROLLER FEATURES:

- pH Monitoring from 6.8 pH to 8.2 pH with .1 pH Resolution
- Set Level from 7.0 pH to 8.0 pH
- Dosing Options from Continuous to up to 15 Minutes
- Factory Set 5 Minute Delay in Timed Feed Mode
- Factory Set High (8.0 pH) and Low (7.0 pH) Alert Levels
- Single Button Calibration
- Overfeed Alert after 30 Minutes in Continuous Feed and 30 Feed Cycles in Timed Feed Mode (Requires Hard Reset)
- Easy to Read, Sun-Bright LED Display
- Configure for Acid or Base (Jumper)
- Compact Package (Approx. 7" x 5" x 3")
- Configured for 120 VAC (Input/Output)
- Flow Switch Compatible
- Bright LED Indicators for Feed, Alert and Flow
- Manufactured in the USA